SOLAR WATER HEATER SYSTEM (SERIES A-FC)

SOLAR WATER FORCED SYSTEM (series A-FC)



Millionsun solar forced circulation system (Series A) flexibly integrates flat plate collectors, water tanks and control system, forming a heating system with closed loop forced split circulation, which is applicable to both household and large scale hot water projects, such as hospitals, hotels and schools.

This system operation Automatic control and operation, safe and convenient

Features

- Stylish slim line design.
- Forced operation minimises maintenance.
- Electric booster models available.
- Stainless steel SUS316 inner tank.
- Collector absorber from Germany Bluetec company.
- Details of the Product and quality is important for us.



Benefits

- Reliable, low maintenance operation.
- Automatic control and operation with user friendly design.
- Flexible solution with options of collector and tank capacity.
- Strong design to withstand the extreme weather condition.
- Easy to mounting and installation.
- Perfect combination with buildings.
- Worklife over 15 years.

Warranty Details: 10 years system

| Туре | A-FC500/8 | A-FC400/6 | A-FC300/4 | A-FC200/3 | A-FC150/2 |
|--------------------|----------------------|-------------------|---------------------------|---------------------------|-------------------|
| Collector type | M-SBC/2.0-blue-A | | | | |
| Tank type | M-ST/(500L-150L)-FAP | | | | |
| Collector quantity | 4 | 3 | 2 | 1 | 1 |
| Collector area | 8.0m ² | 6.0m ² | 4.0 m ² | 3.0 m ² | 2.0m ² |
| Tank capacity | 500L | 400L | 300L | 200L | 150L |
| Control system | 1 set | 1 set | 1 set | 1 set | 1 set |
| System weight | 310kg | 250kg | 180kg | 150kg | 120kg |
| 20GP/40GP | 12/26 | 17/38 | 21/45 | 32/66 | 39/80 |